BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images, please do not report the images to the Image Problem Mailbox.

ABSTRACT OF THE DISCLOSURE

To provide a transflective liquid crystal display device capable of obtaining a display with a high brightness, a high contrast, and a wide viewing ~~angle. According to the liquid crystal display device of the present invention, the~~ angle, a vertical alignment mode using liquid crystal ~~layer 50~~ layer whose initial alignment state represents a vertical alignment is utilized, the reflective display ~~region R~~ region is provided to surround the periphery of the transmissive display ~~region T~~ region within a single dot region, and an insulating ~~film 21~~ film for regulating the thickness of the liquid crystal layer is provided in a region corresponding to the reflective display region R in the periphery of the dot. In addition, in the substrate (counter ~~substrate 25)~~ substrate) opposite to the side where the insulating ~~film 21~~ film is formed, an ~~opening 31s~~ opening is provided in a common ~~electrode 31~~ electrode at a position corresponding to the boundary between the reflective display ~~region R~~ region and the transmissive display ~~region T.~~ region.